2 Door Mega Top Sandwich / Salad Prep Refrigerator

Features



High quality 430 stainless steel exterior and 304 stainless steel interior provide both durability and beauty to the unit.

Recessed Handle

Recessed along the entire door handle which provides strength and durability to the door to prevent damage/breakage during excessive opening.

3/4" Thick Cutting Board One of the thickest and best cutting boards in the industry. Comes standard with unit.

Digital Temperature Controls The LCD display allows for temperature control and easy visual read out.

* Does not include pans.



2 Adjustable Interior Shelf

The interior shelf sits on adjustable mounting brackets to allow for height adjustments to accommodate different sized products.

4 Casters

They include 2 front locking casters and come pre-installed for easy set up. Also allows for easy moving during cleaning or maintenance.

Self Closing Door(s)

Self closing door keeps energy costs down by not allowing as much cold air to escape the unit while opening. The door also has an auto stop feature that keeps door open when at 90 degrees to make for easier loading and unloading.

Models	Doors	#of Shelves	H/P	AMPS	Gross Weight	WDH
SST-48-18	2	2	1/3	8.1	370 lbs	46.75" x 34" x 46.25"



TECHNICAL DATA

Dimensions

Exterior Dimensions (WxDxH)
Interior Dimensions Top (WxDxH)
Interior Dimensions Bottom (WxDxH)
Cutting Board Dimensions (WxDxH)
Net Volume (cu. ft.)
Gross Weight
Packaging Dimensions (WxDxH)
Electrical Cord Length

46.75" x 34" x 46.25" 42.5" x 21.5" x 8.5" 43" x 19.5" x 20" 46.75" x 7.0" x .75" 12 cu. ft. 370 lbs 51.5" x 38.5" x 49.5"

84"

Cooling

Temperature Range 32° - 40° F
Refrigerant R134a
Maximum Ambient 100.4° F
Temperature Rating
Defrosting Automatic
Temperature Display Yes
Temperature Controller Digital
H/P 1/3

Construction

Exterior Material 430 series stainless steel
Interior Material 304 series stainless steel
Insulation Material Foamed in place polyurethane
Shelf Material Plastic coated steel

Shelf Load Capacity 90 lbs *Does not include pans

Electrical

Voltage 120 Amps 8.1 Hz 60 Phase 1

PLAN VIEW







